

RECTIFIERS

For Metal Finishing

British made for reliability



**A good practical range of small to medium sized process rectifiers, solidly built to give reliable service over many years of use.
Built in the UK to high standards using UK sourced parts.**

SPECIFICATION

Case: 1.2mm thick folded and welded steel. Light Grey hammer finished epoxy powder coated. Rating IP54. Hinged door with seals and locks, can be wall or base mounted.

Meters: Analogue 72 x 72mm DIN, moving coil. Digital 50 x 25mm 0.1 amp/volts

Transformers: UK wound, 100% duty cycle. Earth protected.

Rectification: Diodes on Heat sinks, fan cooled.

Overload rating = maximum current x 10 (momentary)

Control: Fully variable 0 - 100%, hand operated transformer.

All parts CE standard.

RECTIFIER SIZES

CODE	TYPE
3416D	Rectifier 25 amp 10 volt, Analogue meters , S/Phase
3417D	Rectifier 50 amp 10 volt, " " " "
3418D	Rectifier 100 amp 10 volt, " " " "
3419D	Rectifier 150 amp 10 volt, " " " "
3421D	Rectifier 200 amp 10 volt, " " " "
3420D	Rectifier 250 amp 10 volt, " " " "
3422D	Rectifier 300 amp 10 volt, " " 3 phase
3429D	Rectifier 600 amp 10 volt, " " 3 phase

Other sizes available up to 10,000 amps / 30 volts or to your specifications.



OPTIONS & EXTRAS.

Digital meters, Process timers, Audible "time out" warning,
Visual "time out" warning. Amp-time controllers, see data sheet DS 16.

We also manufacture Amp time meters, process tanks, temperature / level controllers fume cabinets and general metal finishing equipment.

FOR FURTHER DETAILS PLEASE CONTACT US.



Engineering Limited

Unit Z, Hamstead Ind Est, Austin Way, Great Barr
Birmingham, B42 1DU, England
Tel: 44 (0)121 358 1456 Fax: 44 (0)121 357 4159
Email: info@balco.co.uk Website: www.balco.co.uk
Manufacturing processing equipment since 1969

